

TECHNICAL SPECIFICATIONS

Recommended Installation	Indoors
Rated load	1000kgs
Rated speed	max 0.15m/sec
Height Limit	max travel height: 13m
	Top Height: 2.3mm
Pit depth	110mm
Stops	5 stops
Standard platform sizes (w x d)	1400 x 2000 / 1400 x 2500 / 1100 x 2200
Standard lift dimentions (w x d)	1830 x 2080 / 1400 x 2580 / 1530 x 2280
Cut-out size	1860 x 2110 / 1430 x 2610 / 1560 x 2310
Other platform dimentions width	1000 - 1400
Other platform dimentions depth	1500 - 2500
Standard shaft finish	Laminated sandwich panels in RAL 9003 (white) (T=25mm, H=565mm), Glazed panels optional.
Standard platform finish	RAL 9003 (white)
	All powder coated, other RAL colors available upon request
	Black rubber flooring
Doors	Swing doors, doors can be on 3 sides
Drive system	Screw and nut
Control system	PLC
Power supply	380-400V 3-phase 50/60 Hz 16A, frequency converter
Motor	4kW
Battery emergency lowering	incl. as standard
Door buttons	One touch
Platform buttons	Automatic
	All buttons with tactile and braile
Certifications	MD 2006 / 42 / EC
Manufactured in	Sweden