

## TECHNICAL SPECIFICATIONS

Recommended Installation	Indoors
Rated load	500kgs
Rated speed	max 0.15m/sec
Height Limit	Max Travel Height: 13m
	Top Height: 2, 3m / 1, 1m
Pit depth	50mm (ramp 50mm optional)
Stops	5 stops
Standard platform sizes (w x d)	1000 x 1500 / 1100 x 1400 / 1100 x 1500 / 1100 x 1600
Standard lift dimentions (w x d)	1370 x 2680 / 1470 x 1480 / 1470 x 1580 / 1470 x 1680
Cut-out size	1425 x 2735 / 1525 x 1535 / 1525 x 1635 / 1525 x 1735
Other platform dimentions width	700 - 1100
Other platform dimentions depth	1100 - 1600
Standard shaft finish	Laminated sandwich panels in RAL 9003 (white) (T=25mm, H=565mm), Glazed panels optional.
Standard platform finish	RAL 9003 (white)
	All powder coated, other RAL colors available upon request
	Black rubber flooring
Doors	Swing doors, doors can be on 3 sides
Drive system	Screw and nut
Control system	PLC
Power supply	380-400V 3-phase 50/60 Hz 16A
	230V 3-phase 50/60 Hz 16A frequently converter as standard
	230V 1-phase 50/60 Hz 16A with frequency converter optional
Motor	2.2 kW
Battery emergency lowering	incl. as standard
Door buttons	One touch
Platform buttons	Automatic
	All buttons with tactile and braile
Certifications	MD 2006 / 42 / EC, EN81-41
Manufactured in	Sweden